

Ex signal calculator

5115B

- Redundancy measurement with 2 input signals
- Signal calculator with the four arithmetical operations
- Duplication of the input signal
- Input for RTD, Ohm, TC, mV, mA, and V
- Universal supply by AC or DC



Application

- Redundancy measurement of temperature by means of two sensors, where the secondary sensor takes over the measurement when a sensor error occurs on the primary sensor.
- Duplication of the input signal, e.g. from a temperature sensor or an analog process signal to two separate analog outputs.
- Signal calculator with four arithmetical operations: Addition, subtraction, multiplication and division.
- Example: Differential measurement: (Input 1 * K1) - (Input 2 * K2) + K4
- Example: Average measurement: (Input 1 * 0.5) + (Input 2 * 0.5) + K4
- Example: Different functions on the outputs: Output 1 = input 1 - input 2, and Output 2 = input 1 + input 2
- I.S. safety barrier and power supply for 2-wire transmitters.


Technical characteristics

- Within a few seconds the user can program PR5115B to a selected application using the configuration program PReset.
- A green front LED indicates normal operation, sensor error on each sensor, and functional error.
- 5-port 3.75 kVAC galvanic isolation.

Mounting / installation

- Mounted vertically or horizontally on a DIN rail. As the devices can be mounted without any distance between neighboring units, up to 42 devices can be mounted per meter.

Connection



Environmental Conditions

Specifications range.....	-20°C to +60°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP20

Mechanical specifications

Dimensions (HxWxD).....	109 x 23.5 x 130 mm
Weight approx.....	225 g
Wire size.....	1 x 2.5 mm ² stranded wire
Screw terminal torque.....	0.5 Nm

Common specifications

Supply voltage, universal.....	21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse.....	400 mA SB / 250 VAC
Max. power consumption.....	≤ 3 W
Internal consumption.....	≤ 2.0 W
Isolation voltage, test / working.....	3.75 kVAC / 250 VAC
Communications interface.....	Loop Link
Signal / noise ratio.....	Min. 60 dB (0...100 kHz)
Response time (0...90%, 100...10%):	
Temperature input (programmable).....	400 ms...60 s
mA / V input (programmable).....	250 ms...60 s
Updating time.....	115 ms (temperature input)
Updating time.....	75 ms (mA / V / mV input)
Redundancy switch-over time.....	≤ 400 ms
Signal dynamics, input.....	22 bit
Signal dynamics, output.....	16 bit
Auxiliary voltages: Reference voltage.....	2.5 VDC ±0.5% / 15 mA
Auxiliary supply: Loop supply (pin 44...42 and 54...52).....	28...17.1 VDC / 0...20 mA
EMC immunity influence.....	< ±0.5% of span
Extended EMC immunity: NAMUR NE 21, A criterion, burst.....	< ±1% of span

Input specifications

Max. offset.....	50% of selected max. value
RTD input.....	Pt100, Ni100, lin. R
Cable resistance per wire (max.), RTD.....	10 Ω
Sensor current, RTD.....	Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire), RTD.....	< 0.002 Ω / Ω
Sensor error detection, RTD.....	Yes
TC input: Thermocouple type.....	B, E, J, K, L, N, R, S, T, U, W3, W5, LR
Cold junction compensation (CJC).....	< ±1.0°C
Sensor error current, TC.....	Nom. 30 μA
Current input: Measurement range.....	0...100 mA
Min. measurement range (span), current input.....	4 mA
Input resistance: Supplied unit.....	Nom. 10 Ω + PTC 10 Ω
Input resistance: Non-supplied unit.....	RSHUNT = ∞, VDROP < 6 V
Voltage input: Measurement range.....	0...250 VDC
Voltage input: Measurement range.....	-150...+150 mV
Min. measurement range (span), voltage input.....	5 mV
Input resistance, voltage input.....	Nom. 10 MΩ (≤ 2.5 VDC)
Input resistance, voltage input.....	Nom. 5 MΩ (> 2.5 VDC)
Input resistance, voltage input.....	Nom. 10 MΩ (mV input)

Output specifications

Current output: Signal range.....	0...20 mA
Min. signal range.....	10 mA
Load (max.).....	20 mA/600 Ω/12 VDC
Load stability, current output.....	≤0.01% of span/100 Ω
Current limit.....	≤ 28 mA
Voltage output: signal range.....	0...10 VDC
Voltage output: min. signal range.....	500 mV
Load (min.).....	500 kΩ
2-wire 4...20 mA output: Signal range.....	4...20 mA
Load stability, 4...20 mA output.....	≤ 0.01% of span / 100 Ω
Effect of external 2-wire supply voltage variation.....	< 0.005% of span / V
Max. external 2-wire supply.....	29 VDC
Sensor error detection, current output.....	Programmable 0...23 mA
NAMUR NE 43 Upscale/Downscale.....	23 mA / 3.5 mA
*of span.....	= Of the presently selected range

Approvals

EMC.....	EN 61326-1
LVD.....	EN 61010-1
PELV/SELV.....	IEC 364-4-41 and EN 60742
ATEX.....	DEMKO 00ATEX128567
GOST R.....	Yes
GOST Ex.....	Yes
DNV Marine.....	Stand. f. Certific. No. 2.4